Revision date: 02.11.2021 Version: GB 8 Page 1 of 11

SECTION 1: NAME OF THE SUBSTANCE OR MIXTURE AND THE COMPANY

1.1 Product identifier

Substance name: Quartz

Synonyms: Silica sand, crystalline silica sand, silicon dioxide, Quartz

sand, Quartzite

Chemical name and formula: SiO2

Trade Names: Crystal quartz sand, kiln-dried or moist direct from

the stockpile, very fine quartz sand (product series

BCS, BVS, GS, GLS, QS, BS, FS, FPS)

CAS number: 14808-60-7 EINECS number: 238-878-4

REACH Registration number: Exempted in accordance with Annex V.7

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Main applications (non exhaustive list):

Paint, ceramics, glass fibre, adhesives, plastics, rubber sealants, special concrete, manufacture of silicon, ferrosilicon and ironoxide pellets. Additive in production of cement and concrete. Fluxing material.

1.2.2 Uses advised against

No use identified in Section 1.2. is advised against

1.3. Details of the supplier of the safety data sheet:

[entity within EU]

Company name: Strobel Quarzsand GmbH

Address: Freihungsand 3, 92271 Freihung, GERMANY

Phone N°: + 49 (0)9646-9201-0 Fax N°: + 49 (0)9646-9201-701

E-mail of competent person responsible for SDS in the MS

or in the EU: guenter.forster@strobel-quarzsand.de

1.4. Emergency telephone number:

European Emergency N°: 112

National Poison Centre telephone United Kingdom: 0344 892 0111

N°: National Poisons Information Service (Cardiff Centre)

Gwenwyn Ward, Llandough Hospital

(Also see national emergency telephone numbers at http://echa.europa.eu/web/guest/support/helpdesks/national-

helpdesks/list-of-national-helpdesks)

Emergency telephone at the

company: +49 (0) 9646/920115



Revision date: 02.11.2021 Version: GB 8 Page 2 of 11

Available outside office hours:

X Yes

Other information (e.g. language

of the phone service): English/German

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP] as amended

Not classified

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

Not classified

2.3. Other hazards

This product is an organic substance and does not meet the criteria for PBT or vPvB as set out in Annex XIII of REACH. No additional hazards identified.

Quartz is not included in the Candidate List of substances of very high concern for Authorisation.

Quartz is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Main constituent:

Quartz

Amount: SiO2 > 98% EINECS number: 238-878-4 CAS number: 14808-60-7

3.2 Impurities

None

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Following eye contact:

Rinse under water for at least one minute and seek medical attention if irritation persists.

Following inhalation:

Movement of the exposed individual from the area to fresh air is recommended.

4.2 Most important symptoms and effects, both acute and delayed:

No acute and delayed symptoms and effects are observed.



Revision date: 02.11.2021 Version: GB 8 Page 3 of 11

4.3 Indication of any immediate medical attention and special treatment needed:

No special measures required.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

No specific extinguishing media is needed.

Unsuitable extinguishing media:

No restriction on the extinguishing media to be used.

5.2 Special hazards arising from the substance or mixture:

Non combustible. No hazardous thermal decomposition.

5.3 Advice for fire fighters:

No specific fire-fighting protection is required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid airborne dust generation, wear respiratory personal protective equipment in compliance with national legislation, see EN 143: 2000.

6.2 Environmental precautions:

No special requirements.

6.3 Methods and material for containment and cleaning up:

Avoid dry sweeping and use water spraying or vacuum cleaning systems (with high-efficiency particulate air filter) to prevent airborne dust generation. Wear personal protective equipment in compliance with national legislation.

6.4 Reference to other sections:

See Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

7.1.1 Protective measures

Avoid airborne dust generation. Provide appropriate exhaust ventilation at places where airborne dust is generated. Other suitable controls may include enclosure, isolation, water suppression, respiratory protective equipment. Handle packaged products carefully to prevent accidental bursting. If you require advice on safe handling techniques, please contact your supplier or check the Good Practice Guide referred to in section 16.



Revision date: 02.11.2021 Version: GB 8 Page 4 of 11

7.1.2 Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Shower and change clothes at end of work shift.

7.2 Conditions for safe storage, including any incompatibilities: Technical measures / precautions

Minimise airborne dust generation and prevent wind dispersal during loading and unloading. Keep containers closed and store packaged products so as to prevent accidental bursting.

7.3 Specific end use(s):

If you require advice on specific uses, please contact your supplier or check the Good Practice Guide referred to in section 16.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Follow workplace regulatory exposure limits for all types of airborne dust (e.g. total dust, respirable dust, respirable crystalline silica dust). The OEL (Occupational Exposure Limit) for respirable crystalline silica dust is 0,1 mg/m³ in Germany, measured as an 8 hour TWA (Time Weighted Average). For the equivalent limits in other countries, please consult a competent occupational hygienist or the local regulatory authority. A European Binding OEL (Occupational Exposure Limit) for respirable crystalline silica dust is set at 0.1 mg/m³ in the Directive (EU) 2017/2398, measured as an 8-hour TWA (Time Weighted Average).

8.2 Exposure controls:

8.2.1 Appropriate engineering controls:

Minimise airborne dust generation. Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Apply organisational measures, e.g. by isolating personnel from dusty areas. Remove and wash soiled clothing.

8.2.2 Individual protection measures such as personal protective equipment:

A) EYE/FACE PROTECTION

Wear safety glasses with side-shields in circumstances where there is a risk of penetrative eye injuries.

B) SKIN PROTECTION

No specific requirement. For hands, see below. Appropriate protection (e.g. protective clothing, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin.

HAND PROTECTION:

Appropriate protection (e.g. gloves, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin. Wash hands at the end of each work session.



Revision date: 02.11.2021 Version: GB 8 Page 5 of 11

C) RESPIRATORY PROTECTION:

In case of prolonged exposure to airborne dust concentrations, wear a respiratory protective equipment that complies with the requirements of European or national legislation. The use of half or full face masks with filters against particles of category 2 or 3 (FP2 - FP3) is recommended. See EN 143: 2000 - Respiratory protective devices. Particle filters

8.2.3 Environmental exposure controls:

Avoid wind dispersal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

a) Physical state: solid/white b) Colour: grayish/white c) Odour: odourless d) Odour threshold not applicable

pH value (400 g/l water at 20°C) 5-8 e) ph value

f) Melting point/freezing point > 1610°C

g) Initial boiling point and boiling range Between 2230 and 2590 °C

h) Flash point Not applicable (solid with a melting point >1610°C) Not applicable (solid with a melting point >1610°C) i) Evaporation rate

Flammability (solid, gaseous) Non-flammable (not combustible) j)

Non explosive (absence of chemical groups associated k) Explosive limits

with explosive properties)

Not applicable (solid with a melting point >1610°C) I) Vapour pressure

m) Vapour density Not applicable n) Relative density 2-3 g/cm3 o) Grain shape Angular p) Solubility in water Negligible q) Solubility in hydrofluoric acid

Yes

r) Partitition coefficient: n-octanol/water Not applicable (inorganic substance)

s) Auto-ignition temperature No self-heating under 400 °C (a solid with a melting point

> 1610 °C)

t) Decomposition temperature Approx. 2000 °C

u) Viscosity Not applicable (solid with a melting point >1610°C)

v) Explosive properties Non explosive (absence of chemical groups associated

with explosive properties)

Not applicable (substance is incapable of reacting w) Oxidising properties

exothermically with a combustible material)

x) Particle characteristics Particle size can be found in the respective technical data

sheet

9.2 Other information:

Not applicable

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

Inert, not reactive

10.2 Chemical stability:

Chemically stable



Revision date: 02.11.2021 Version: GB 8 Page 6 of 11

10.3 Possibility of hazardous reactions:

No hazardous reactions.

10.4 Conditions to avoid:

Not relevant

10.5 Incompatible materials:

No particular incompatibilities.

10.6 Hazardous decomposition products:

Not relevant



Revision date: 02.11.2021 Version: GB 8 Page 7 of 11

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicity endpoints	Outcome of the effects assessment
Acute toxicity	The acute oral/dermal LD50 value of quartz and cristobalite is greater than 2000 mg/kg.
	Acute toxicity on inhalation: There is no specific acute toxicity data at doses that enable a categorical decision on the acute inhalation toxicity classification for any form of crystalline silica at 100%. Acute inhalation toxicity is not expected based on read across to an OECD compliant study, with a substance that contains 45% cristobalite and gives no indication of lethality. Hence further testing is not warranted in the interests of animal welfare.
Skin corrosion / irritation Serious eye damage / irritation	Quartz (coarse sand and milled) is not irritating to skin (OECD TG 404). Quartz (coarse sand and milled) is not irritating to eye (OECD TG 405).
Respiratory or skin sensitisation	No evidence of skin sensitisation in handbook data.
Germ cell mutagenicity	Quartz has a genotoxic and mutagenic effect mainly through its inflammatory effects. Respirable quartz was unable to cause increased HPRT mutations in rat lung epithelial cells in vitro.
Carcinogenicity	Lung cancer excess risk is demonstrated only under high occupational exposures to Respirable Crystaline Silica. The lung cancer excess risk is restricted to subjects who contracted silicosis.
Reproductive toxicity	Silica is essential for normal body function and is ingested orally via the consumption of foods containing silica naturally. An early one-generation study on Wistar rats gave no evidence of any adverse effects arising from long-term feeding of silica-rich water.
STOT - single exposure	Available studies; inconclusive
STOT - repeated exposure	This product is not classified as STOT RE according to criteria defined in the Regulation EC 1272/2008. Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica. There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see section 16 below for more information).
Aspiration hazard	No aspiration hazard envisaged



Revision date: 02.11.2021 Version: GB 8 Page 8 of 11

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Available data for the substance have been considered against the criteria laid down in Regulations ((EC) No 1907/2006, (EU) 2017/2100, (EU) 2018/605) and found not to apply

11.2.2 Other information

None

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity:

Not relevant

12.2 Persistence and degradability:

Not relevant

12.3. Bioaccumulative potential

Not relevant

12.4. Mobility in soil

Negligible

12.5. Results of PBT and vPvB assessment

Not relevant

12.6. Endocrine disrupting properties

Available data for the substance have been considered against the criteria laid down in Regulations ((EC) No 1907/2006, (EU) 2017/2100, (EU) 2018/605) and found not to apply.

12.7. Other adverse effects

No specific adverse effects known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

WASTE FROM RESIDUES/UNUSED PRODUCTS

Where possible, recycling is preferable to disposal. Can be disposed of in compliance with local regulations.

PACKAGING

Dust formation from residues in packaging should be avoided and suitable worker protection assured. Store used packaging in enclosed receptacles. Recycling and disposal of packaging should be carried out in compliance with local regulations. The re-use of packaging is not recommended. Recycling and disposal of packaging should be carried out by an authorised waste management company.



Revision date: 02.11.2021 Version: GB 8 Page 9 of 11

SECTION 14: TRANSPORT INFORMATION

14.1 UN-Number:

Not relevant

14.2. UN proper shipping name

Not relevant

14.3. Transport hazard classes

ADR: not classified IMDG: not classified

ICAO/IATA: not classified

RID: not classified

14.4. Packaging group

Not relevant

14.5. Environmental hazards

Not relevant

14.6. Special precautions for the user

No special precautions.

14.7. Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture National legislations:

Wassergefährdungsklasse: NWG

15.2. Chemical safety assessment

Exempted from REACH Registration in accordance with Annex V.7. of Regulation (EC) 1907/2006.

SECTION 16: OTHER INFORMATION

Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.

16.1. Revision

Most of the 16 Sections have been updated and formatted according to the revised ECHA Guidance on the compilation of safety data sheets (version 3 of February 2015). Therefore, this SDS has been completely redrafted and replaced the former SDS (version GB 7) supplied. The SDS has been revised to comply with Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of REACH.



Revision date: 02.11.2021 Version: GB 8 Page 10 of 11

16.2. Abbreviations

LD50: Medial lethal dose.

PBT: Persistent bioaccumulative toxic STOT: Specific Target Organ Toxicity vPvB: Very persistent very bioaccumulative

OEL: Occupational exposure level

SDS: Safety data sheet

16.3. Relevant H-statements

Not applicable

16.4. Other relevant information

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In 2009, in the Monographs 100 series, IARC confirmed its classification of Silica Dust, Crystalline, in the form of Quartz and Cristobalite (IARC Monographs, Volume 100C, 2012).

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003).

A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers.

Works involving exposure to respirable crystalline silica dust generated by a work process are included in Directive (EU) 2017/2398 of 12 December 2017 amending Directive 2004/37/EC on the Protection of Workers from the risks related to exposure to Carcinogens or Mutagens at work.

Health & Safety Executive (specific for UK): Detailed reviews of the scientific evidence on the health effects of crystalline silica have been published by HSE (Health and Safety Executive, UK) in the Hazard Assessment Documents EH75/4 (2002) and EH75/5 (2003). The HSE points out on its website that "Workers exposed to fine dust containing quartz are at risk of developing a chronic and possibly severely disabling lung disease known as "silicosis". In addition to



Revision date: 02.11.2021 Version: GB 8 Page 11 of 11

silicosis, there is now evidence that heavy and prolonged workplace exposure to dust containing crystalline silica can lead to an increased risk of lung cancer. The evidence suggests that an increased risk of lung cancer is likely to occur only in those workers who have developed silicosis.

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.

END OF THE SAFETY DATA SHEET

